

Essential Commands

gdb *program* [*core*] debug *program* [using coredump *core*]
b [*file:*]*function* set breakpoint at *function* [in *file*]
run [*arglist*] start your program [with *arglist*]
bt backtrace: display program stack
p *expr* display the value of an expression
c continue running your program
n next line, stepping over function calls
s next line, stepping into function calls

Starting GDB

gdb start GDB, with no debugging files
gdb *program* begin debugging *program*
gdb *program core* debug coredump *core* produced by *program*
gdb --help describe command line options

Stopping GDB

quit exit GDB; also **q** or **EOF** (eg **C-d**)
INTERRUPT (eg **C-c**) terminate current command, or send to running process

Getting Help

help list classes of commands
help *class* one-line descriptions for commands in *class*
help *command* describe *command*

Executing your Program

run *arglist* start your program with *arglist*
run start your program with current argument list
run ... <*inf*> *outf* start your program with input, output redirected
kill kill running program

tty *dev* use *dev* as stdin and stdout for next **run**
set **args** *arglist* specify *arglist* for next **run**
set **args** specify empty argument list
show **args** display argument list

show **environment** show all environment variables
show **env** *var* show value of environment variable *var*
set **env** *var string* set environment variable *var*
unset **env** *var* remove *var* from environment

Shell Commands

cd *dir* change working directory to *dir*
pwd Print working directory
make ... call "make"
shell *cmd* execute arbitrary shell command string

[] surround optional arguments ... show one or more arguments

Breakpoints and Watchpoints

break [*file:*]*line* set breakpoint at *line* number [in *file*]
b [*file:*]*line* eg: **break** *main.c:37*
break [*file:*]*function* set breakpoint at *function* [in *file*]
break **+offset** set break at *offset* lines from current stop
break **-offset**
break ***addr** set breakpoint at address *addr*
break set breakpoint at next instruction
break ... **if** *expr* break conditionally on nonzero *expr*
cond *n* [*expr*] new conditional expression on breakpoint *n*; make unconditional if no *expr*
tbreak ... temporary break; disable when reached
rbreak *regex* break on all functions matching *regex*
watch *expr* set a watchpoint for expression *expr*
catch *x* break at C++ handler for exception *x*

info **break** show defined breakpoints
info **watch** show defined watchpoints

clear delete breakpoints at next instruction
clear [*file:*]*fun* delete breakpoints at entry to *fun()*
clear [*file:*]*line* delete breakpoints on source line
delete [*n*] delete breakpoints [or breakpoint *n*]

disable [*n*] disable breakpoints [or breakpoint *n*]
enable [*n*] enable breakpoints [or breakpoint *n*]
enable **once** [*n*] enable breakpoints [or breakpoint *n*]; disable again when reached
enable **del** [*n*] enable breakpoints [or breakpoint *n*]; delete when reached

ignore *n* *count* ignore breakpoint *n*, *count* times

commands *n* execute GDB *command-list* every time breakpoint *n* is reached. [**silent** suppresses default display]
end end of *command-list*

Program Stack

backtrace [*n*] print trace of all frames in stack; or of *n* frames—innermost if *n*>0, outermost if *n*<0
bt [*n*]
frame [*n*] select frame number *n* or frame at address *n*; if no *n*, display current frame
up *n* select frame *n* frames up
down *n* select frame *n* frames down
info **frame** [*addr*] describe selected frame, or frame at *addr*
info **args** arguments of selected frame
info **locals** local variables of selected frame
info **reg** [*rn*]... register values [for regs *rn*] in selected frame; **all-reg** includes floating point
info **all-reg** [*rn*]
info **catch** exception handlers active in selected frame

Execution Control

continue [*count*] continue running; if *count* specified, ignore this breakpoint next *count* times
c [*count*]
step [*count*] execute until another line reached; repeat *count* times if specified
s [*count*]
stepi [*count*] step by machine instructions rather than source lines
si [*count*]
next [*count*] execute next line, including any function calls
n [*count*]
nexti [*count*] next machine instruction rather than source line
ni [*count*]
until [*location*] run until next instruction (or *location*)
finish run until selected stack frame returns
return [*expr*] pop selected stack frame without executing [setting return value]
signal *num* resume execution with signal *s* (none if 0)
jump *line* resume execution at specified *line* number or *address*
jump ***address**
set **var**=*expr* evaluate *expr* without displaying it; use for altering program variables

Display

print [*/f*] [*expr*] show value of *expr* [or last value *f*] according to format *f*:
p [*/f*] [*expr*]
x hexadecimal
d signed decimal
u unsigned decimal
o octal
t binary
a address, absolute and relative
c character
f floating point
call [*/f*] *expr* like **print** but does not display **void**
x [*/Nuf*] *expr* examine memory at address *expr*; optional format spec follows slash
N count of how many units to display
u unit size; one of
b individual bytes
h halfwords (two bytes)
w words (four bytes)
g giant words (eight bytes)
f printing format. Any **print** format, or
s null-terminated string
i machine instructions
disassem [*addr*] display memory as machine instructions

Automatic Display

display [*/f*] *expr* show value of *expr* each time program stops [according to format *f*]
display display all enabled expressions on list
undisplay *n* remove number(s) *n* from list of automatically displayed expressions
disable **disp** *n* disable display for expression(s) number *n*
enable **disp** *n* enable display for expression(s) number *n*
info **display** numbered list of display expressions

Expressions

expr an expression in C, C++, or Modula-2 (including function calls), or:
addr@len an array of *len* elements beginning at *addr*
file::nm a variable or function *nm* defined in *file*
{ *type* } *addr* read memory at *addr* as specified *type*
\$ most recent displayed value
\$n *n*th displayed value
\$\$ displayed value previous to **\$**
\$\$\$n *n*th displayed value back from **\$**
\$_ last address examined with **x**
\$_ value at address **\$_**
\$_var convenience variable; assign any value

show values [*n*] show last 10 values [or surrounding **\$n**]
show convenience display all convenience variables

Symbol Table

info address *s* show where symbol *s* is stored
info func [*regex*] show names, types of defined functions (all, or matching *regex*)
info var [*regex*] show names, types of global variables (all, or matching *regex*)
whatis [*expr*] show data type of *expr* [or **\$**] without evaluating; **p***type* gives more detail
p*type* [*expr*] describe type, struct, union, or enum

GDB Scripts

source *script* read, execute GDB commands from file *script*
define *cmd* create new GDB command *cmd*; execute *script* defined by *command-list*
command-list
end end of *command-list*
document *cmd* create online documentation for new GDB *command cmd*
help-text
end end of *help-text*

Signals

handle *signal act* specify GDB actions for *signal*:
print announce signal
noprint be silent for signal
stop halt execution on signal
nostop do not halt execution
pass allow your program to handle signal
nopass do not allow your program to see signal
info signals show table of signals, GDB action for each

Debugging Targets

target *type param* connect to target machine, process, or file
help target display available targets
attach *param* connect to another process
detach release target from GDB control

Controlling GDB

set *param value* set one of GDB's internal parameters
show *param* display current setting of parameter

Parameters understood by **set** and **show**:

complaints *limit* number of messages on unusual symbols
confirm *on/off* enable or disable cautionary queries
editing *on/off* control **readline** command-line editing
height *lpp* number of lines before pause in display
language *lang* Language for GDB expressions (**auto**, **c** or **modula-2**)
listsize *n* number of lines shown by **list**
prompt *str* use *str* as GDB prompt
radix *base* octal, decimal, or hex number representation
verbose *on/off* control messages when loading symbols
width *cpl* number of characters before line folded
write *on/off* Allow or forbid patching binary, core files (when reopened with **exec** or **core**)
history ... groups with the following options:
h ... disable/enable **readline** history expansion
h file *filename* file for recording GDB command history
h size *size* number of commands kept in history list
h save *off/on* control use of external file for command history
print ... groups with the following options:
p ...
p address *on/off* print memory addresses in stacks, values
p array *off/on* compact or attractive format for arrays
p demangl *on/off* source (demangled) or internal form for C++ symbols
p asm-dem *on/off* demangle C++ symbols in machine-instruction output
p elements *limit* number of array elements to display
p object *on/off* print C++ derived types for objects
p pretty *off/on* struct display: compact or indented
p union *on/off* display of union members
p vtbl *off/on* display of C++ virtual function tables
show commands show last 10 commands
show commands n show 10 commands around number *n*
show commands + show next 10 commands

Working Files

file [*file*] use *file* for both symbols and executable; with no arg, discard both
core [*file*] read *file* as coredump; or discard
exec [*file*] use *file* as executable only; or discard
symbol [*file*] use symbol table from *file*; or discard
load *file* dynamically link *file* and add its symbols
add-sym *file addr* read additional symbols from *file*, dynamically loaded at *addr*
info files display working files and targets in use
path *dirs* add *dirs* to front of path searched for executable and symbol files
show path display executable and symbol file path
info share list names of shared libraries currently loaded

Source Files

dir *names* add directory *names* to front of source path
dir clear source path
show dir show current source path
list show next ten lines of source
list - show previous ten lines
list lines display source centered around *lines*, specified as one of:
[*file:*] *num* line number [in named file]
[*file:*] *function* beginning of function [in named file]
+off *off* lines after last printed
-off *off* lines previous to last printed
***address** line containing *address*
list f,l from line *f* to line *l*
info line num show starting, ending addresses of compiled code for source line *num*
info source show name of current source file
info sources list all source files in use
forw *regex* search following source lines for *regex*
rev *regex* search preceding source lines for *regex*

GDB under GNU Emacs

M-x gdb run GDB under Emacs
C-h m describe GDB mode
M-s step one line (**step**)
M-n next line (**next**)
M-i step one instruction (**steppi**)
C-c C-f finish current stack frame (**finish**)
M-c continue (**cont**)
M-u up *arg* frames (**up**)
M-d down *arg* frames (**down**)
C-x & copy number from point, insert at end
C-x SPC (in source file) set break at point

GDB License

show copying Display GNU General Public License
show warranty There is NO WARRANTY for GDB. Display full no-warranty statement.

Copyright ©1991, 1992 Free Software Foundation, Inc.
Roland Pesch (pesch@cygnus.com), January 1992—Revision: 1.96
The author assumes no responsibility for any errors on this card.

This card may be freely distributed under the terms of the GNU General Public License.

Please contribute to development of this card by annotating it.

GDB itself is free software; you are welcome to distribute copies of it under the terms of the GNU General Public License. There is absolutely no warranty for GDB.