

# YUML and YPL Database Manual

Don Batory  
**batory@cs.utexas.edu**  
 November 2016



## 1 YUML

Yuml is a free web service that draws UML class diagrams given a Yuml input specification. As this is a for-profit company, the "free" service comes with some strings attached. Namely, it will produce a pretty class diagram for you provided that your specification is not too complicated. (I found other problems with Yuml, but this is a story for another day).

Familiarize yourself with Yuml:

- go to the Yuml Class Diagram Web site
- type in this spec:  

```
[student|name]has-likes[course|name]
```
- and Yuml returns this gorgeous diagram:



Fig. 1: Student-Course Diagram.

Draw some diagrams of your own. When you feel comfortable, proceed to the next section.

## 2 YUML SPECIFICATIONS

A Yuml specification is elegant. Here is a BNF of a subset of Yuml that MDElite6 uses. Literals (*aka*, tokens) are in single 'quotes'.

```

// YumlSpec is 1 or more lines
YumlSpec : Line+ ;

// and each line defines a box or connection
Line : Box | Connection ;

Box : '[' Class ']' ;

// read left-2-right, ignore numbers
Connection : BoxName [End1] [Role1] DashType
            [Role2] [End2] BoxName ;

// BoxName = class or interface name
BoxName : '[' String ']'
         | '[' 'interface;' String ']'
         ;

DashType : '-' // solid line
         | '-.-' // dashed line
         ;
  
```

```

End : '<>' // aggregation
     | '++' // composition
     | '^' // inheritance
     | '<' // left arrow
     | '>' // right arrow
     ;

// String that has no ']' and quote chars
Role : String ;

// name only, name+meths only, name+flds+meths
Class : Name
      | Name '|' String
      | Name '|' String '|' String
      ;

// String that has no ']' and quote chars
Name : String ;
  
```

Note that a String token is mentioned above. This not a Java String, but one that is devoid of the characters:

- comma ','
- left brace '['
- right brace ']'
- less than '<'
- greater than '>'
- minus '-'

Further, a semicolon ";" means new line. Some hints:

- Since Yuml doesn't like "[[]" as in "String[[]]", I use "#" – so "String[[]]" becomes "String#".
- Since Yuml doesn't like commas (as in "foo(int x, int y)"), I simply use blanks between types – like "foo(int int)".
- Since Yuml has no indicator to distinguish static from non-static, I simply preface the names of static members with an underscore – like "\_bar()".

So, the following Yuml specification (a sentence in the above language):

```

[Interface;Closable|close()]
[Interface;NetworkChannel]
    bind();getLocalAddress();getOption();
    setOption();supportedOptions()
[MyClass|_MyClass();close()]
[Interface;Closable]^-.-[MyClass]
[YourClass]<>-3>[MyClass]
[interface;Closable]^-[Interface;NetworkChannel]
  
```

Produces the beauty of Figure 2 when Yuml draws it.




Fig. 2: Another Yuml Diagram.

**Warning!** Do not read the above specification too deeply! 'Interface;Closable' is a String. The word 'Interface' means nothing to Yuml. It could just as well have been 'George', which also means nothing to Yuml. What Yuml does understand is ';' (semicolon), which means add a new line. So 'Interface;Closable' produces a 2-line name in the above figure. And the string 'bind();getLocalAddress()' means print strings 'bind()' and 'getLocalAddress()' on separate lines.

### 3 THE YPL SCHEMA

Here is the YPL schema (ypl.schema.pl), which can encode YUML diagrams as a database of tuples:<sup>1</sup>

```

dbase(yuml, [yumlClass, yumlInterface, yumlAssociation]).

table(yumlClass, [id, "name", "fields", "methods"]).
table(yumlInterface, [id, "name", "methods"]).
table(yumlAssociation, ["name1", "role1", "end1",
    "name2", "role2", "end2"]).
  
```

Here is a MDL.ClassYumlParser translation of (ie, the database of tuples that encodes) the specification of Figure 1:

```

dbase(ypl, [yumlClass, yumlInterface, yumlAssociation]).

table(yumlClass, [id, "name", "fields", "methods"]).
yumlClass(c0, 'student', 'name', '').
yumlClass(c1, 'course', 'name', '').

table(yumlInterface, [id, "name", "methods"]).

table(yumlAssociation, [id, "name1", "role1", "end1", "name2", "role2", "end2"]).
yumlAssociation(id0, 'student|name', 'has', '', 'course|name', 'loves', '').
  
```

And here is a MDL.ClassYumlParser translation of the specification of Figure 2:

```

dbase(ypl, [yumlClass, yumlInterface, yumlAssociation]).

table(yumlClass, [id, "name", "fields", "methods"]).
yumlClass(c2, 'MyClass', '_MyClass();close()', '').
yumlClass(c3, 'YourClass', '', '').

table(yumlInterface, [id, "name", "methods"]).
yumlInterface(c1, ';NetworkChannel', '').
yumlInterface(c4, ';Closable', '').
yumlInterface(c0, ';Closable', '').
  
```

1. I have broken lines in code listings in this document for presentation reasons. Generally, the MDElite6 parser expects one complete declaration per line.

```

table(yumlAssociation, [id, "name1", "role1", "end1",
    "name2", "role2", "end2"]).
yumlAssociation(id0, ';Closable', '', '^', 'MyClass', '', '').
yumlAssociation(id1, 'YourClass', '', '<>', 'MyClass', '3', '>').
yumlAssociation(id2, 'Closable', '', '^', 'NetworkChannel',
    '', '').
  
```

Of course, you can take these databases and convert them into Yuml specs using the MDElite6 MDL.ClassYumlUnParser. See MDElite6 documentation for more details.

### 4 YPL CONSTRAINTS

There indeed are YPL constraints. I have not posted them, as they are good examples for homework assignments.

### 5 CLOSING

This tool is a work in progress. It is possible that this documentation may get out-of-date with code releases. If so, just report them to me and I will try to fix them a.s.a.p. — dsb